NSN 5999-01-069-9669



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-069-9669 **Body Style:** Rectangular **Body Length:** 0.785 inches **Body Width:** 0.320 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.330 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** 25.000 volts **Material And Location:** Plastic, epoxy resin body Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.300 inches **Mounting Facility:** Terminal **Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 0.500 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 50.000 nanoseconds single section **Segment Quantity Per Section:**

10 single section

Segment Delay Time:

5.000 nanoseconds single section all segments

NSN 5999-01-069-9669

Delay Line - Page 2 of 2



Pu	lse	Rise	Time	Rating	1:

7.5 nanoseconds

Terminal Type And Quantity:

14 wire leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100