## NSN 5999-01-076-4691

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-076-4691

| Cross Sectional Shape:  |
|---|
| Emi composition   |
| Hole Diameter:  |
| 0.250 inches  |
| Overall Length:   |
| 16.860 inches   |
| Tempurature Rating:   |
| -45.0 degrees fahrenheit and 220.0 degrees fahrenheit   |
| Overall Width:  |
| 15.000 inches   |
| Minor Width:  |
| 0.125 inches  |
| Outside Corner Radius:  |
| 0.620 inches  |
| Aperture Width:   |
| 14.862 inches   |
| Aperture Length:  |
| 16.722 inches   |
| Outside Edge To Bolt Hole Center Distance Along Width:  |
| 0.310 inches  |
| Outside Edge To Bolt Hole Center Distance Along Length:   |
| 0.310 inches  |
| Cross-sectional Height:   |
| 0.125 inches  |
| Minor Height:   |
| 0.100 inches  |
| Bolt Hole Quantity:   |
| 32  |
| Environmental Protection Material Location:   |
| Throughout rf shielding gasket  |
| Material:   |
| Rubber chloroprene class cr environmental seal  |
| Material Specification:   |
| Qq-n-281, class b federal specification single material response emi/rfi conductor or ams 4730 a assn standard single material response   |
| emi/rfi conductor   |
| Style Designator:   |
| Non-circular Section 1. The section |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |

No

## NSN 5999-01-076-4691

Electronic Shielding Gasket - Page 2 of 2



Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6855 spec.