## NSN 5999-01-078-9603



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-078-9603 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.880 inches **Body Width:** 0.310 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** Any acceptable **Operating Tempurature Range:** Not rated **Mounting Facility Quantity:** 14 **Voltage Rating:** 50.000 volts **Material And Location:** Plastic, epoxy resin body Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.280 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Electromechanical **Delay Time Variation Method:** 

Tapped **Section Delay Time:** 

30.000 nanoseconds single section

## NSN 5999-01-078-9603

Delay Line - Page 2 of 2



Segment Quantity Per Section:
10 single section
Segment Delay Time:
3.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
3.0 nanoseconds
Terminal Type And Quantity:
14 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

**Fiig:** A32100