

View Online at <https://aerobasegroup.com/nsn/5999-01-080-6486>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

0.525 inches

Body Width:

0.225 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.041 inches

Longest Vertical Distance Between Mounting Centers:

0.100 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

12

Voltage Rating:

50.000 volts

Material And Location:

Any acceptable

Surface Treatment And Location:

Any acceptable

Input Impedance Rating:

50.000 ohms

Output Impedance Rating:

50.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

Any acceptable

Mounting Facility:

Pin

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

5.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

40.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

4.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

6.5 nanoseconds

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100