

View Online at <https://aerobasegroup.com/nsn/5999-01-080-6486>

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

0.525 inches

**Body Width:**

0.225 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.041 inches

**Longest Vertical Distance Between Mounting Centers:**

0.100 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Mounting Facility Quantity:**

12

**Voltage Rating:**

50.000 volts

**Material And Location:**

Any acceptable

**Surface Treatment And Location:**

Any acceptable

**Input Impedance Rating:**

50.000 ohms

**Output Impedance Rating:**

50.000 ohms

**Frequency Bandwidth:**

Not rated

**Body Depth:**

Any acceptable

**Mounting Facility:**

Pin

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

5.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

40.000 nanoseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

4.000 nanoseconds single section all segments

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

6.5 nanoseconds

**Terminal Type And Quantity:**

12 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100