NSN 5999-01-082-9842



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-082-9842 **Body Style:** Rectangular **Body Length:** 1.000 inches **Body Width:** 0.320 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.800 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity: Material And Location:** Plastic, epoxy resin body Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Body Depth:** 0.320 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 0.500 Signal Delay Method: Lumped constant **Section Delay Time:** 100.000 nanoseconds single section **Pulse Rise Time Rating:** 30.0 nanoseconds **Terminal Type And Quantity:** 3 wire leads **Test Data Document:** 81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a

Unit Of Measure:

NSN 5999-01-082-9842

Delay Line - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32100