## NSN 5999-01-086-8120

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-086-8120 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Operating Tempurature Range:** -0.0/+70.0 degrees celsius **Voltage Rating:** Between 2.000 volts and 8.000 volts **Material And Location:** Plastic, diallyl phthalate, mil-m-14, type sdg body Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.250 inches **Mounting Facility:** Plug-in **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 25.000 nanoseconds single section **Segment Quantity Per Section:** 5 single section

**Segment Delay Time:** 

4.000 nanoseconds single section all segments

**Delay Time Variation Per Deg Celsius:** 

Not rated

**Pulse Rise Time Rating:** 

4.0 nanoseconds

## NSN 5999-01-086-8120

Delay Line - Page 2 of 2



<b>Terminal</b>	<b>Type</b>	And	Quantity:
-----------------	-------------	-----	-----------

8 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100