NSN 5999-01-098-3301

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-098-3301

| Overall Length: |
|---|
| Between 0.767 inches and 0.797 inches |
| Pin Diameter: |
| 0.040 inches |
| Overall Diameter: |
| Between 0.082 inches and 0.085 inches |
| Cable Entrance Diameter: |
| Between 0.022 inches and 0.025 inches |
| End Application: |
| C-130, c-5, c-141 |
| Pin Length: |
| 0.437 inches |
| Current Rating In Amps: |
| 2.5 |
| Mounting Method: |
| Force fit |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essential |
| Material: |
| Copper alloy body and contact |
| Material Specification: |
| Mil-c-23216 military specification single material response body and contact |
| Precious Material And Location: |
| Body and contact surfaces gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Surface Treatment: |
| Gold body and contact and nickel body and contact |
| Surface Treatment Specification: |
| Mil-g-45204, type 2, grade c, class 1 military specification single treatment response body and contact |
| Style Designator: |
| Pin contact |
| Terminal Type And Quantity: |
| 1 crimp end opposite contact |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5999-01-098-3301

Electrical Contact - Page 2 of 2



Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-c-23216 spec.