NSN 5999-01-100-3868

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-100-3868

| Body Style: |
|---|
| Rectangular |
| Slot Length: |
| 0.018 inches |
| Frequency Rating: |
| Not rated |
| Body Length: |
| 0.800 inches |
| Body Width: |
| 0.400 inches |
| Individual Section Quantity: |
| 5 |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Mounting Facility Quantity: |
| 8 |
| Voltage Rating: |
| Between 4.500 volts and 5.500 volts |
| Material And Location: |
| Any acceptable |
| Input Impedance Rating: |
| Not rated |
| Output Impedance Rating: |
| Not rated |
| Frequency Bandwidth: |
| Not rated |
| Body Depth: |
| 0.280 inches |
| Mounting Facility: |
| Slotted hole |
| Attenuation In Decibels: |
| Not rated |
| Signal Delay Method: |
| Electromechanical |
| Delay Time Variation Method: |
| Variable |
| Section Delay Time: |
| 500.000 nanoseconds 5th section err-100 |
| Delay Time Variation Per Deg Celsius: |
| Not rated |
| Pulse Rise Time Rating: |
| 4.0 nanoseconds |

NSN 5999-01-100-3868

Delay Line - Page 2 of 2



| Terminal Type And Quantity | Terminal | Type | And | Quantity | / : |
|----------------------------|----------|-------------|-----|----------|------------|
|----------------------------|----------|-------------|-----|----------|------------|

8 solder stud

Err Default:

Err default

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100