NSN 5999-01-105-1668

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-105-1668 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 2.500 inches **Body Width:** 0.560 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Encased **Mounting Facility Quantity: Voltage Rating:** 25.000 volts **Material And Location:** Brass terminal err-100 err-100 or copper terminal err-100 err-100 **Surface Treatment And Location:** Tinned terminal Input Impedance Rating: 75.000 ohms **Output Impedance Rating:** 75.000 ohms Frequency Bandwidth: 39000.0 kilohertz **Body Depth:** 0.500 inches **Mounting Facility: Attenuation In Decibels:** 1.000 **Signal Delay Method:** Inductance **Delay Time Variation Method:** Tapped

200.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Section Delay Time:

NSN 5999-01-105-1668

Delay Line - Page 2 of 2



Segment De	elay Time:
------------	------------

20.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

20.0 nanoseconds

Terminal Type And Quantity:

13 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100