## NSN 5999-01-106-0843



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-106-0843 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.187 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Longest Vertical Distance Between Mounting Centers:** 0.325 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** 25.000 volts **Material And Location:** Plastic, epoxy resin body Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms Frequency Bandwidth: Not rated **Body Depth:** Any acceptable **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 0.500 **Signal Delay Method:** Inductance **Delay Time Variation Method:** 

Tapped

**Section Delay Time:** 

50.000 nanoseconds single section

## NSN 5999-01-106-0843

Delay Line - Page 2 of 2



Segment Quantity Per Section:
10 single section
Segment Delay Time:
5.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
6.5 nanoseconds
Terminal Type And Quantity:
14 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

**Fiig:** A32100