# NSN 5999-01-106-4658

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-106-4658

Body Style:

Rectangular

**Frequency Rating:** 

Not rated

# **Body Length:**

0.780 inches

# **Body Width:**

0.260 inches

# Individual Section Quantity:

1

# Longest Horizontal Distance Between Mounting Centers:

Any acceptable

# Longest Vertical Distance Between Mounting Centers:

0.300 inches

# **Operating Tempurature Range:**

# -55.0/+105.0 degrees celsius

Voltage Rating:

# 100.000 volts

# Material And Location:

Plastic, epoxy resin body

# Input Impedance Rating:

100.000 ohms

#### **Output Impedance Rating:**

100.000 ohms

#### Frequency Bandwidth:

Not rated

# **Body Depth:**

0.200 inches

# **Mounting Facility:**

Terminal

# Mounting Provision Arrangement Style:

Four position rectangular

#### Attenuation In Decibels:

Not rated

# Signal Delay Method:

Lumped constant

# **Delay Time Variation Method:**

Tapped

#### Section Delay Time:

10.000 nanoseconds single section

# Segment Quantity Per Section:

10 single section

# NSN 5999-01-106-4658

Delay Line - Page 2 of 2



Segment Delay Time:

1.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.2 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32100