NSN 5999-01-106-4658



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-106-4658 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.780 inches **Body Width:** 0.260 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Voltage Rating:** 100.000 volts **Material And Location:** Plastic, epoxy resin body Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.200 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 10.000 nanoseconds single section

Segment Quantity Per Section: 10 single section

NSN 5999-01-106-4658

Delay Line - Page 2 of 2



Segment Delay Time:

1.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.2 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100