

View Online at <https://aerobasegroup.com/nsn/5999-01-108-7857>

**Body Style:**

Rectangular, front connection

**Overall Depth:**

0.426 inches

**Body Length:**

Between 0.740 inches and 0.780 inches

**Body Width:**

0.300 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Voltage Rating:**

5.000 volts

**Material And Location:**

Plastic, epoxy case

**Output Impedance Rating:**

200.000 ohms

**Body Depth:**

0.187 inches

**Mounting Facility:**

Plug-in

**Attenuation In Decibels:**

6.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

150.000 nanoseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

15.000 nanoseconds single section all segments

**Pulse Rise Time Rating:**

30.0 nanoseconds

**Terminal Type And Quantity:**

14 pin

**Test Data Document:**

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100