

View Online at <https://aerobasegroup.com/nsn/5999-01-108-7857>

Body Style:

Rectangular, front connection

Overall Depth:

0.426 inches

Body Length:

Between 0.740 inches and 0.780 inches

Body Width:

0.300 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Rating:

5.000 volts

Material And Location:

Plastic, epoxy case

Output Impedance Rating:

200.000 ohms

Body Depth:

0.187 inches

Mounting Facility:

Plug-in

Attenuation In Decibels:

6.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

150.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

15.000 nanoseconds single section all segments

Pulse Rise Time Rating:

30.0 nanoseconds

Terminal Type And Quantity:

14 pin

Test Data Document:

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100