

View Online at <https://aerobasegroup.com/nsn/5999-01-109-3292>

**Individual Section Quantity:**

10

**End Application:**

An/mpl/4k

**Input Impedance Rating:**

100.000 ohms

**Output Impedance Rating:**

100.000 ohms

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

60.000 nanoseconds single section

**Pulse Rise Time Rating:**

7.500 nanoseconds

**Terminal Type And Quantity:**

12 pin

**Special Features:**

Dimensions 0.760 in. Length, 0.290 in. Width, 0.225 in. Height, taps are 0.008-0.012 in. Thick and 0.160-0.200 in. Total length, heads are 0.200-0.300 in. Long and 0.050 in. Wide and shaft is 0.020 in. Wide, pins are 0.100in. Apart center to center, 2 common, 1 input and 10 taps, common pins are 0.035 in. Wide, pins project downward from body at a width of 0.290-0.310 in. At body to 0.300-0.350 in. At lowest point, half circle 0.035 in. Radius is cut of center of width dimension on top

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100