## NSN 5999-01-111-1466

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-111-1466 **Body Style:** Rectangular **Body Length:** 0.710 inches **Body Width:** 0.400 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius Voltage Rating: 25.000 volts **Surface Treatment And Location:** Gold terminal Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms **Body Depth:** 0.175 inches **Mounting Facility: Terminal Attenuation In Decibels:** 0.200 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 50.000 nanoseconds single section **Segment Quantity Per Section:** 10 single section **Segment Delay Time:** 5.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 10.0 nanoseconds **Terminal Type And Quantity:** 14 tab solder lug **Precious Material And Location:** 

Terminal surface gold

**Precious Material:** 

Gold

## NSN 5999-01-111-1466

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100