NSN 5999-01-114-1376

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-114-1376

C	0	.: 1	Chana.
UIUSS.	340	uonai	Shape:

Mesh and composition

Hole Diameter:

Between 0.115 inches and 0.135 inches

Overall Length:

Between 20.230 inches and 20.250 inches

Overall Width:

Between 12.990 inches and 13.010 inches

Minor Width:

Between 0.115 inches and 0.135 inches

Aperture Width:

Between 11.740 inches and 11.760 inches

Aperture Length:

Between 18.980 inches and 19.000 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 4.990 inches and 5.010 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 4.990 inches and 5.010 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.330 inches and 0.350 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.330 inches and 0.350 inches

Cross-sectional Height:

Between 0.115 inches and 0.135 inches

Minor Height:

Between 0.115 inches and 0.135 inches

Bolt Hole Quantity:

12

Environmental Protection Material Location:

Around rf shielding gasket aperture

Material:

Rubber silicone class q environmental seal

Material Specification:

Qq-n-281 federal specification single material response emi/rfi conductor

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5999-01-114-1376

Electronic Shielding Gasket - Page 2 of 2



Fiig:

A032a0

Mil-std (military Standard):

Mil-r-5847 spec.