

View Online at <https://aerobasegroup.com/nsn/5999-01-115-7556>

**Body Style:**

Rectangular

**Slot Length:**

0.020 inches

**Adjustment Device Quantity:**

1

**Adjustment Device Drive Type:**

Slotted screw

**Body Length:**

Between 1.374 inches and 1.434 inches

**Body Width:**

Between 0.485 inches and 0.515 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.300 inches

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4

**Voltage Rating:**

50.000 pounds per hour wet

**Input Impedance Rating:**

100.000 ohms

**Body Depth:**

Between 0.297 inches and 0.327 inches

**Mounting Facility:**

Terminal

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

1.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

0.000 nanoseconds single section and 160.000 nanoseconds single section

**Segment Quantity Per Section:**

1 single section

**Delay Time Variation Per Deg Celsius:**

0.010 nanoseconds

**Pulse Rise Time Rating:**

32.0 nanoseconds

**Terminal Type And Quantity:**

4 pin

**Err Default:**

Err default

**Special Test Features:**

Selected and tested for an/tpx-42 (v) 10

**Test Data Document:**

00752-505174 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32100