

View Online at <https://aerobasegroup.com/nsn/5999-01-115-7556>

Body Style:

Rectangular

Slot Length:

0.020 inches

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

Between 1.374 inches and 1.434 inches

Body Width:

Between 0.485 inches and 0.515 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.300 inches

Longest Vertical Distance Between Mounting Centers:

1.000 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4

Voltage Rating:

50.000 pounds per hour wet

Input Impedance Rating:

100.000 ohms

Body Depth:

Between 0.297 inches and 0.327 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

0.000 nanoseconds single section and 160.000 nanoseconds single section

Segment Quantity Per Section:

1 single section

Delay Time Variation Per Deg Celsius:

0.010 nanoseconds

Pulse Rise Time Rating:

32.0 nanoseconds

Terminal Type And Quantity:

4 pin

Err Default:

Err default

Special Test Features:

Selected and tested for an/tpx-42 (v) 10

Test Data Document:

00752-505174 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100