Electronic Shielding Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-120-2898

Hole Diameter:

0.190 inches

Overall Length:

24.250 inches

Overall Width:

15.120 inches

Aperture Width:

13.620 inches

Aperture Length:

22.750 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.350 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.360 inches

Cross-sectional Thickness:

0.120 inches

Bolt Hole Quantity:

24

Outside Edge To Inside Edge Smallest Distance Along Width:

Between 0.630 inches and 0.870 inches

Outside Edge To Inside Edge Smallest Distance Along Length:

Between 0.630 inches and 0.870 inches

Special Features:

Gasket matl: rubber, sponge, silicone, closed cell, grade m per specification mil-r-46089; rfi shield matl: rubber, sponge, silicone, closed cell, grade f per specification mil-r-46089, covered with a continuous braid of electrically conductive 32 gauge monel metal wires per specification qq-n-281; 0.750 length when rfi shield is bonded to gasket; hole pattern is not symmetrical; gasket must be continuous so as to form a rfi/emi and water tight seal when compressed between two parallel surfaces; used on dsests

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A032a0