NSN 5999-01-122-4943

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-122-4943

Body Style:
Rectangular
Frequency Rating:
Not rated
Body Length:
0.785 inches
Body Width:
0.290 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Rating:
25.000 volts
Surface Treatment And Location:
Electroplated tin lead solder terminal or hot dipped tin lead solder terminal or bright acid tin plate terminal
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
0.300 inches
Mounting Facility:
Terminal
Attenuation In Decibels:
0.500
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
47.500 nanoseconds single section
Segment Quantity Per Section:
2 single section
Segment Delay Time:
25.000 nanoseconds single section 2nd segment err-100
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:

6.0 nanoseconds

NSN 5999-01-122-4943

Delay Line - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

14 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100