

View Online at <https://aerobasegroup.com/nsn/5999-01-123-5429>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

0.785 inches

Body Width:

0.290 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Rating:

Not rated

Surface Treatment And Location:

Electro-plated tin-lead solder terminal or hot dipped tin lead solder terminal or bright acid tin plate terminal

Input Impedance Rating:

50.000 ohms

Output Impedance Rating:

50.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

Any acceptable

Mounting Facility:

Terminal, wire-lead

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

55.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

9.000 nanoseconds single section 9th segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.6 nanoseconds

Terminal Type And Quantity:

2 wire leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100