NSN 5999-01-124-0070

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-124-0070

Identification Code Color:					
Black and red					
Overall Length:					
0.531 inches					
Pin Diameter:					
Between 0.091 inches and 0.094 inches					
Overall Diameter:					
Between 0.091 inches and 0.094 inches					
Cable Entrance Diameter:					
0.031 inches					
Pin Length:					
0.248 inches					
Mounting Method:					
Terminal					
Crimping Tool Identifying Number:					
M22520/1-01					
Criticality Code Justification:					
Feat					
Special Features:					
Color band toward pin shall be black, band toward crimp well shall be red					
Material:					
Copper alloy body and contact					
Precious Material And Location:					
Body and contact surfaces gold					
Precious Material And Weight:					
0.005 gold grains, troy					
Precious Material:					
Gold					
Surface Treatment:					
Gold body and contact and nickel body and contact					
Surface Treatment Specification:					
Mil-g-45204 military specification 1st treatment response body and contact					
Style Designator:					
Pin contact					
Test Data Document:					
81349-mil-c-39029 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification					
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain					
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And					
18876-+39029-009-01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer					
drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)					

Terminal Type And Quantity: 1 crimp end opposite contact

Purchase Description Identification:

•

18876-p39029-009-01

Chalf Life.

NSN 5999-01-124-0070

Electrical Contact - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-g-45204 spec.