NSN 5999-01-124-2510

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-124-2510

Overall Length:
1.088 inches
Overall Height:
0.025 inches
Overall Width:
0.073 inches
Voltage Rating In Volts:
300.0 ac
Slot Accommodation Width:
0.006 inches
Pin Accommodation Length:
0.164 inches
Current Rating In Amps:
3.0
Mounting Method:
Terminal
Material:
Beryllium body and contact
Material Specification:
Qq-c-533 federal specification 1st material response body and contact and mil-h-7199 military specification 2nd material response body and
contact
Precious Material And Location:
Body and contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Surface Treatment:
Gold body and contact and nickel body and contact
Surface Treatment Specification:
Mil-g-45204, type 1, grade c, class 1 military specification 1st treatment response body and contact and qq-n-290, class 2 federal
specification 2nd treatment response body and contact
Style Designator:
Irregular shape
Test Data Document:
81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 wire wrap axially at one end

Specification Data:

81349-mil-c-28754/37 government specification

Shelf Life:

N/a

NSN 5999-01-124-2510

Electrical Contact - Page 2 of 2



Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-h-7199 spec.