

View Online at <https://aerobasegroup.com/nsn/5999-01-124-2510>

Overall Length:

1.088 inches

Overall Height:

0.025 inches

Overall Width:

0.073 inches

Voltage Rating In Volts:

300.0 ac

Slot Accommodation Width:

0.006 inches

Pin Accommodation Length:

0.164 inches

Current Rating In Amps:

3.0

Mounting Method:

Terminal

Material:

Beryllium body and contact

Material Specification:

Qq-c-533 federal specification 1st material response body and contact and mil-h-7199 military specification 2nd material response body and contact

Precious Material And Location:

Body and contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Gold body and contact and nickel body and contact

Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification 1st treatment response body and contact and qq-n-290, class 2 federal specification 2nd treatment response body and contact

Style Designator:

Irregular shape

Test Data Document:

81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 wire wrap axially at one end

Specification Data:

81349-mil-c-28754/37 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A222a0

Mil-std (military Standard):

Mil-h-7199 spec.