Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-125-6411

Overall Length:

0.518 inches

Overall Diameter:

0.062 inches

Cable Entrance Diameter:

0.0345 inches

Pin Accommodation Length:

0.166 inches

Pin Accommodation Diameter:

0.034 inches

Mounting Method:

Terminal

Material:

Copper alloy body and contact

Material Specification:

Qq-b-626 federal specification single material response body and contact or qq-m-321 federal specification single material response body and contact or qq-b-750 federal specification single material response body and contact or qq-c-530 federal specification single material response body and contact or qq-c-533 federal specification single material response body and contact

Precious Material And Location:

Body and contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Gold body and contact

Surface Treatment Specification:

Mil-g-45204, type 2, class 2, grade c military specification single treatment response body and contact

Style Designator:

Center contact

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 crimp axially at one end

Specification Data:

81349-mil-c-55302/65 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5999-01-125-6411

Electrical Contact - Page 2 of 2

Mil-std (military Standard):

Mil-g-45204 spec.

