## NSN 5999-01-127-7872

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-127-7872

| Cross Sectional Shape:  |
|---|
| Emi   |
| Hole Diameter:  |
| 0.141 inches  |
| Overall Length:   |
| 0.840 inches  |
| Tempurature Rating:   |
| -45.0 degrees celsius and 125.0 degrees celsius   |
| Overall Width:  |
| 0.840 inches  |
| Aperture Diameter:  |
| 0.630 inches  |
| Outside Corner Radius:  |
| 0.123 inches  |
| Center To Center Distance Between Bolt Holes Along Width:                                     |
| 0.594 inches  |
| Center To Center Distance Between Bolt Holes Along Length:                                    |
| 0.594 inches  |
| Outside Edge To Bolt Hole Center Distance Along Width:  |
| 0.123 inches  |
| Outside Edge To Bolt Hole Center Distance Along Length:                                       |
| 0.123 inches  |
| Cross-sectional Height:   |
| 0.032 inches  |
| Bolt Hole Quantity:   |
| 4   |
| Environmental Protection Material Location:   |
| Throughout rf shielding gasket  |
| Functional Description:   |
| Provides rfi/environmental seal   |
| Material:   |
| Rubber silicone class q environmental seal  |
| Material Specification:   |
| Zz-r-765, class 2, grade 40 federal specification single material response environmental seal |
| Precious Material And Location:   |
| Throughout rf shielding gasket silver   |
| Precious Material:  |
| Silver  |
| Surface Treatment:  |
| Silver emi/rfi conductor  |
| Style Designator:   |
| Non-circular  |

## NSN 5999-01-127-7872

Electronic Shielding Gasket - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A032a0