## NSN 5999-01-130-1993

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-130-1993 **Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 3.200 volts **Material And Location:** Plastic, diallyl phthalate, mil-m-14, type sdg case **Surface Treatment And Location:** Any acceptable case **Body Depth:** 0.200 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Inductance **Delay Time Variation Method: Tapped Section Delay Time:** 1000.000 nanoseconds single section 200.000 nanoseconds single section all segments

**Segment Quantity Per Section:** 5 single section **Segment Delay Time: Pulse Rise Time Rating:** 3.0 nanoseconds **Terminal Type And Quantity:** 8 pin

## NSN 5999-01-130-1993

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100