

View Online at <https://aerobasegroup.com/nsn/5999-01-130-4006>

Body Style:

Rectangular

Body Length:

0.890 inches

Body Width:

0.450 inches

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

0.700 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

+0.0/+125.0 degrees celsius

Mounting Facility Quantity:

16

Voltage Rating:

Between 4.500 volts and 5.500 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sgd case

Surface Treatment And Location:

Any acceptable case

Body Depth:

0.375 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

Section Delay Time:

300.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

60.000 nanoseconds single section all segments

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100