

View Online at <https://aerobasegroup.com/nsn/5999-01-131-1819>

**Thread Class:**

2a

**Thread Pitch Diameters:**

+0.0997/+0.1177 inches

**Body Style:**

Rectangular

**Body Length:**

2.000 inches

**Body Width:**

1.190 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.688 inches

**Operating Temperature Range:**

-55.0/+95.0 degrees celsius

**Stud Length:**

0.470 inches

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

2

**Voltage Rating:**

150.000 volts

**Material And Location:**

Metal case

**Surface Treatment And Location:**

Enamel, mil-e-15090, type 1, class 2 case

**Input Impedance Rating:**

500.000 ohms

**Output Impedance Rating:**

500.000 ohms

**Body Depth:**

1.190 inches

**Unpackaged Unit Weight:**

7.000 ounces

**Mounting Facility:**

Threaded stud

**Mounting Provision Arrangement Style:**

2 position in-line

**Attenuation In Decibels:**

6.000

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Variable

**Section Delay Time:**

10.000 microseconds single section

**Delay Time Variation Per Deg Celsius:**

0.500 microseconds

**Pulse Rise Time Rating:**

1.79 microseconds

**Terminal Type And Quantity:**

3 wire hook

**Test Data Document:**

81349-mil-d-23859/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Size And Series/type Designator:**

0.138-32 unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100