

View Online at <https://aerobasegroup.com/nsn/5999-01-131-1819>

Thread Class:

2a

Thread Pitch Diameters:

+0.0997/+0.1177 inches

Body Style:

Rectangular

Body Length:

2.000 inches

Body Width:

1.190 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.688 inches

Operating Temperature Range:

-55.0/+95.0 degrees celsius

Stud Length:

0.470 inches

Inclosure Type:

Encased

Mounting Facility Quantity:

2

Voltage Rating:

150.000 volts

Material And Location:

Metal case

Surface Treatment And Location:

Enamel, mil-e-15090, type 1, class 2 case

Input Impedance Rating:

500.000 ohms

Output Impedance Rating:

500.000 ohms

Body Depth:

1.190 inches

Unpackaged Unit Weight:

7.000 ounces

Mounting Facility:

Threaded stud

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

6.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

10.000 microseconds single section

Delay Time Variation Per Deg Celsius:

0.500 microseconds

Pulse Rise Time Rating:

1.79 microseconds

Terminal Type And Quantity:

3 wire hook

Test Data Document:

81349-mil-d-23859/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Size And Series/type Designator:

0.138-32 unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100