## NSN 5999-01-133-7479

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-133-7479 **Body Style:** Rectangular **Body Length:** 1.310 inches **Body Width:** Between 0.500 inches and 0.610 inches **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** 1.114 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.590 inches and 0.620 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 24 **Voltage Rating:** 50.000 volts **Material And Location:** Fiberglass, epoxy case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms **Body Depth:** 0.325 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Variable **Section Delay Time:** 300.000 nanoseconds single section

24 pin

**Terminal Type And Quantity:** 

## NSN 5999-01-133-7479

Delay Line - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100