NSN 5999-01-133-9645



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-133-9645 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.820 inches **Body Width:** 0.410 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** Any acceptable **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Mounting Facility Quantity:** 8 **Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Any acceptable case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.283 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** Not rated

Signal Delay Method: Inductance

Delay Time Variation Method:

Tapped

NSN 5999-01-133-9645

Delay Line - Page 2 of 2



Section Delay Time:
500.000 nanoseconds single section
Segment Quantity Per Section:
5 single section
Segment Delay Time:
100.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
4.0 nanoseconds
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A32100