NSN 5999-01-134-3038

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-134-3038

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

0.820 inches

Body Width:

0.410 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

Any acceptable

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Tempurature Range:

+0.0/+70.0 degrees celsius

Mounting Facility Quantity:

8

Voltage Rating:

Between 4.500 volts and 5.500 volts

Material And Location:

Any acceptable case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.283 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Inductance

Delay Time Variation Method:

Tapped

NSN 5999-01-134-3038

Delay Line - Page 2 of 2



Section Delay Time:

250.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

50.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100