## NSN 5999-01-135-7390

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-135-7390 **Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.600 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 5.000 volts **Material And Location:** Any acceptable case **Surface Treatment And Location:** Any acceptable case **Body Depth:** 0.250 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Solid state **Delay Time Variation Method: Tapped Section Delay Time:** 75.000 nanoseconds single section **Segment Quantity Per Section:** 3 single section **Segment Delay Time:** 25.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 3.0 nanoseconds

6 pin

**Terminal Type And Quantity:** 

## NSN 5999-01-135-7390

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100