

View Online at <https://aerobasegroup.com/nsn/5999-01-144-3480>

Body Style:

Rectangular

Body Length:

0.750 inches

Body Width:

0.300 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Mounting Facility Quantity:

14

Material And Location:

Fiberglass, epoxy body and nickel-copper alloy, qq-n-281, class a terminal

Surface Treatment And Location:

Tin plate terminal

Input Impedance Rating:

160.000 ohms

Output Impedance Rating:

160.000 ohms

Body Depth:

0.187 inches

Mounting Facility:

Pin

Attenuation In Decibels:

8.000

Signal Delay Method:

Lumped constant

Section Delay Time:

500.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

5.000 nanoseconds

Pulse Rise Time Rating:

100.0 nanoseconds

Terminal Type And Quantity:

14 pin

Test Data Document:

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100