NSN 5999-01-146-3970

Electrical Contact - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-146-3970

| Overall Length: |
|---|
| Between 0.526 inches and 0.546 inches |
| Overall Diameter: |
| Between 0.082 inches and 0.085 inches |
| Voltage Rating In Volts: |
| 1000.0 dc |
| Pin Accommodation Length: |
| Between 0.290 inches and 0.310 inches |
| Pin Accommodation Diameter: |
| Between 0.069 inches and 0.073 inches |
| Current Rating In Amps: |
| 5.0 |
| Mounting Method: |
| Force fit |
| Special Features: |
| One 0.025 in. Min to 0.033 in. Maximum diameter hole located on one side of contact end |
| Material: |
| Steel body |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Surface Treatment: |
| Gold contact and nickel contact |
| Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response contact |
| Style Designator: |
| Socket contact |
| Terminal Type And Quantity: |
| 1 crimp axially at one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A222a0 |
| Mil-std (military Standard): |

Mil-g-45204 spec.