NSN 5999-01-147-7025

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-147-7025 **Body Style:** Rectangular **Body Length:** 0.750 inches **Body Width:** 0.270 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.700 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** +0.0/+80.0 degrees celsius **Inclosure Type:** Encased **Mounting Facility Quantity:** 14 **Voltage Rating:** 50.000 volts **Material And Location:** Fiberglass, epoxy case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: 200.000 ohms **Output Impedance Rating:** 200.000 ohms **Body Depth:** 0.230 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 18.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method:**

Tapped

Section Delay Time:

200.000 nanoseconds single section

NSN 5999-01-147-7025

Delay Line - Page 2 of 2



Segment	Quantity	Per	Section:
Segment	Quantity	Per	Section:

10 single section

Segment Delay Time:

20.000 nanoseconds single section all segments

Pulse Rise Time Rating:

40.0 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100