

View Online at <https://aerobasegroup.com/nsn/5999-01-147-7025>

Body Style:

Rectangular

Body Length:

0.750 inches

Body Width:

0.270 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.700 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

+0.0/+80.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Quantity:

14

Voltage Rating:

50.000 volts

Material And Location:

Fiberglass, epoxy case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

200.000 ohms

Output Impedance Rating:

200.000 ohms

Body Depth:

0.230 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

18.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

200.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

20.000 nanoseconds single section all segments

Pulse Rise Time Rating:

40.0 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100