NSN 5999-01-149-2558

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-149-2558 **Body Style:** Rectangular, top connection **Overall Width:** 0.395 inches Frequency Rating: Not rated **Body Length:** 0.870 inches **Body Width:** 0.245 inches **Individual Section Quantity: Operating Tempurature Range:** -0.0/+70.0 degrees celsius **End Application:** An/gsq-204processing system, signal **Mounting Facility Quantity:** 16 **Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Any acceptable case **Surface Treatment And Location:** Any acceptable case Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.400 inches **Mounting Facility:** Terminal, wire-lead **Attenuation In Decibels:** Not rated **Signal Delay Method:** Inductance **Delay Time Variation Method:** Tapped **Section Delay Time:**

125.000 nanoseconds single section

NSN 5999-01-149-2558

Delay Line - Page 2 of 2



Segment Quantity Per Section:
5 single section
Segment Delay Time:
25.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
3.0 nanoseconds
Terminal Type And Quantity:
16 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A32100