# NSN 5999-01-149-2558

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-149-2558

## Body Style:

Rectangular, top connection

## **Overall Width:**

0.395 inches

# Frequency Rating:

Not rated

# **Body Length:**

0.870 inches

## **Body Width:**

0.245 inches

## Individual Section Quantity:

1

### **Operating Tempurature Range:**

-0.0/+70.0 degrees celsius

#### **End Application:**

An/gsq-204processing system, signal

## **Mounting Facility Quantity:**

16

Voltage Rating:

Between 4.500 volts and 5.500 volts

## Material And Location:

Any acceptable case

# Surface Treatment And Location:

Any acceptable case

## Input Impedance Rating:

Not rated

### **Output Impedance Rating:**

Not rated

### Frequency Bandwidth:

Not rated

### Body Depth:

0.400 inches

#### **Mounting Facility:**

Terminal, wire-lead

### Attenuation In Decibels:

Not rated

## Signal Delay Method:

Inductance

## **Delay Time Variation Method:**

Tapped

### Section Delay Time:

125.000 nanoseconds single section

# NSN 5999-01-149-2558

Delay Line - Page 2 of 2



Segment Quantity Per Section: 5 single section Segment Delay Time: 25.000 nanoseconds single section all segments Delay Time Variation Per Deg Celsius: Not rated Pulse Rise Time Rating: 3.0 nanoseconds Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A32100