NSN 5999-01-152-1707

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-152-1707 **Thread Class:** 2b **Body Style:** Rectangular **Body Length:** Between 4.344 inches and 4.406 inches **Body Width:** 3.250 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.000 inches **Operating Tempurature Range:** -5.0/+85.0 degrees celsius **Mounting Facility Quantity: Voltage Rating:** 2.000 volts Input Impedance Rating: 20000.000 ohms **Output Impedance Rating:** 2000.000 ohms Frequency Bandwidth: Between 0.5 kilohertz and 7.0 kilohertz **Body Depth:** 1.625 inches **Mounting Facility:** Threaded insert **Mounting Provision Arrangement Style:** 2 position in-line **Attenuation In Decibels:** 11.500 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:**

150.700 microseconds 1st section and 257.200 microseconds 2nd section and 312.300 microseconds 3rd section

Terminal Type And Quantity:

18 pin

Thread Size And Series/type Designator:

0.138-32 unc

NSN 5999-01-152-1707

Delay Line - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100