

View Online at <https://aerobasegroup.com/nsn/5999-01-153-7633>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

0.825 inches

Body Width:

0.400 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.600 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

2350-01-089-1261 gun air defense

Inclosure Type:

Encased

Mounting Facility Quantity:

8

Voltage Rating:

7.000 volts

Material And Location:

Plastic, mil-m-14, type sgd-f case

Surface Treatment And Location:

Plastic, epoxy

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.400 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

Not rated

Signal Delay Method:

Solid state

Delay Time Variation Method:

Tapped

Section Delay Time:

38.500 nanoseconds single section and 206.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

77.500 nanoseconds single section 2nd segment err-100 and 82.500 nanoseconds single section 2nd segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100