

View Online at <https://aerobasegroup.com/nsn/5999-01-153-7633>

**Body Style:**

Rectangular

**Frequency Rating:**

Not rated

**Body Length:**

0.825 inches

**Body Width:**

0.400 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.600 inches

**Longest Vertical Distance Between Mounting Centers:**

0.300 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**End Application:**

2350-01-089-1261 gun air defense

**Inclosure Type:**

Encased

**Mounting Facility Quantity:**

8

**Voltage Rating:**

7.000 volts

**Material And Location:**

Plastic, mil-m-14, type sgd-f case

**Surface Treatment And Location:**

Plastic, epoxy

**Input Impedance Rating:**

Not rated

**Output Impedance Rating:**

Not rated

**Frequency Bandwidth:**

Not rated

**Body Depth:**

0.400 inches

**Mounting Facility:**

Terminal

**Mounting Provision Arrangement Style:**

Four position rectangular

**Attenuation In Decibels:**

Not rated

**Signal Delay Method:**

Solid state

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

38.500 nanoseconds single section and 206.000 nanoseconds single section

**Segment Quantity Per Section:**

5 single section

**Segment Delay Time:**

77.500 nanoseconds single section 2nd segment err-100 and 82.500 nanoseconds single section 2nd segment err-100

**Delay Time Variation Per Deg Celsius:**

Not rated

**Pulse Rise Time Rating:**

4.0 nanoseconds

**Terminal Type And Quantity:**

8 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100