# NSN 5999-01-153-9539

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-153-9539

Body Style:
Rectangular
Frequency Rating:
500.000 hertz
Body Length:
0.780 inches
Body Width:
Between 0.245 inches and 0.255 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
0.700 inches
Longest Vertical Distance Between Mounting Centers:
0.300 inches
Operating Tempurature Range:
-55.0/+95.0 degrees celsius
Inclosure Type:
Encased
Mounting Facility Quantity:
16
Voltage Rating:
25.000 volts
Material And Location:
Plastic case
Surface Treatment And Location:
Any acceptable case
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Body Depth:
0.210 inches
Mounting Facility:
Terminal
Mounting Provision Arrangement Style:
Four position rectangular
Attenuation In Decibels:
1.000
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped

## NSN 5999-01-153-9539

Delay Line - Page 2 of 2



Section Delay Time:

15.000 nanoseconds single section

### Segment Quantity Per Section:

10 single section

Segment Delay Time:

1.500 nanoseconds single section all segments

Pulse Rise Time Rating:

3.0 nanoseconds

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

### Fiig:

A32100