

View Online at <https://aerobasegroup.com/nsn/5999-01-154-2541>

Body Style:

Rectangular

Frequency Rating:

500.000 hertz

Body Length:

0.780 inches

Body Width:

Between 0.245 inches and 0.255 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.700 inches

Longest Vertical Distance Between Mounting Centers:

0.300 inches

Operating Temperature Range:

-55.0/+95.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Quantity:

16

Voltage Rating:

25.000 volts

Material And Location:

Plastic case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

0.210 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

1.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

10.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

1.000 nanoseconds single section all segments

Pulse Rise Time Rating:

2.0 nanoseconds

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100