NSN 5999-01-160-6524

Delay Line - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5999-01-160-6524

Rectangular
Frequency Rating:
Not rated
Body Length:
1.000 inches
Body Width:
0.565 inches
Individual Section Quantity:
2
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Mounting Facility Quantity:
10
Voltage Rating:
3.000 volts
Material And Location:
Plastic, mil-m-14, type sdg-f case
Surface Treatment And Location:
Tin plate, mil-t-10727, type 1 or 2 terminal
Input Impedance Rating:
200.000 ohms
Output Impedance Rating:
200.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
0.300 inches
Mounting Facility:
Terminal, wire-lead
Attenuation In Decibels:
1.500
Signal Delay Method:
Lumped constant
Section Delay Time:
900.000 nanoseconds all sections
Segment Quantity Per Section:
3 all sections
Segment Delay Time:
350.000 nanoseconds all sections 3rd segment err-100
Delay Time Variation Per Deg Celsius:
Not rated

NSN 5999-01-160-6524

Delay Line - Page 2 of 2



Pulse Rise	Time	Ratin	g:
------------	------	-------	----

50.0 nanoseconds

Terminal Type And Quantity:

10 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32100