

View Online at <https://aerobasegroup.com/nsn/5999-01-161-3415>

Body Style:

Rectangular

Body Length:

0.725 inches

Body Width:

0.290 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.700 inches

Longest Vertical Distance Between Mounting Centers:

0.325 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

Jetds type an/wlr-8 receiving set countermeasures

Inclosure Type:

Encased

Mounting Facility Quantity:

14

Voltage Rating:

25.000 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sdg case

Surface Treatment And Location:

Any acceptable case

Input Impedance Rating:

200.000 ohms

Output Impedance Rating:

200.000 ohms

Body Depth:

0.225 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

Four position rectangular

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

22.500 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

2.500 nanoseconds single section all segments

Pulse Rise Time Rating:

2.3 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100