## NSN 5999-01-164-2542

Delay Line - Page 1 of 2

**Body Style:** Rectangular

Frequency Rating:



View Online at https://aerobasegroup.com/nsn/5999-01-164-2542

Not rated
Body Length:
Any acceptable
Body Width:
0.280 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Mounting Facility Quantity:
16
Voltage Rating:
Not rated
Input Impedance Rating:
500.000 ohms
Output Impedance Rating:
500.000 ohms
Frequency Bandwidth:
Not rated
Body Depth:
Any acceptable
Mounting Facility:
Terminal
Attenuation In Decibels:
Not rated
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
300.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
30.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
60.0 nanoseconds

## NSN 5999-01-164-2542

Delay Line - Page 2 of 2



Terminal '	Type And	Quantity:
ı errilili ar	I VDE AIIU	Qualitity.

16 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100